

Standard Feature	25 T	35 T	50 T	55 T	65 T
Maximum Capacity	1" dia. thru 5/16" mild steel	1" dia. thru 1/2" mild steel	1" dia. thru 5/8" mild steel	1-1/16" dia. thru 5/8" mild steel	1" dia. thru 3/4" mild steel
Total Depth	5-1/2"	7"	7"	7-1/2"	8-7/8"
Stroke	1"	1-3/8"	1-15/16"	1-1/4"	1-1/4"
Power Requirement	1 phase 120V	1 phase or 3 phase 208V - 575V	1 phase or 3 phase 208V - 575V	1 phase or 3 phase 208V - 575V	1 phase or 3 phase 208V - 575V
Face Size	Optional Accessor	1/2" x 6" 3/8" x 10"	1/2" x 10" 3/4" x 4"	1/2" x 12" 3/4" x 14"	3/4" x 4" 1/2" x 12"
Angle Size	Optional Accessor	3" x 3" x 1/4"	3" x 3" x 3/8" 4" x 4" x 1/4"	3" x 3" x 3/8" 4" x 4" x 1/4"	3" x 3" x 1/2" 4" x 4" x 3/8"
Capacity	Optional Accessor	Optional Accessor	2" x 3" x 5/16"	Optional Accessor	2-1/2" x 4" x 3/8"

DEPENDABLE • AFFORDABLE • VERSATILE



Ironworker Accessories